



Flexible Circuit & Heater Design Guide



all flex
FLEXIBLE CIRCUITS

www.allflexinc.com

Download from our website:
www.allflexinc.com

TABLE OF CONTENTS

BENEFITS OF FLEXIBLE CIRCUITRY	2
Benefits, Advantages, and Features	
ALL FLEX'S STANDARD CAPABILITIES	3 - 4
Design Considerations and Manufacturing Capabilities	
Standard Materials	
SINGLE-SIDED AND DOUBLE-SIDED CIRCUIT CONSTRUCTION	5
Cross Sectional View, Features	
When to Use Single-Sided and Double-Sided Flex	
MULTI-LAYER AND RIGID FLEX CIRCUIT CONSTRUCTION	6
When to Use Multi-Layer and Rigid-Flex	
MAXI-FLEX®	7
Features of these exceptionally long circuits 40' +	
FLEXIBLE HEATER CIRCUITS.....	8-11
Flexible Heater and Hybrid Heaters	
ADDED VALUE CAPABILITIES	12
Automated Pick and Place, Circuit Testing and Potted Circuits	
SURFACE DIELECTRICS OPTIONS	13
Coverlays	
Liquid Photoimageable Soldermask	
DESIGN GUIDELINES.....	14-15
Conductor Pad Design- Fillets, Tie-Downs, and Annular Rings	
Shaved and Elongated Pads, Radiused Traces, and I-Beam	
SHIELDING	16-17
Solid Copper, Cross Hatched Copper	
Conductive Silver	
Conductive Shielding Film	
Stripline Impedance Chart	
RIGIDIZERS/STIFFENERS.....	18
FR4, Polyimide, and Polyester	
TERMINATION METHODS	19
ZIF End and Surface Mount	
All Flex Fingers	
ADDITIONAL TECHNICAL INFORMATION	20 - 22
Typical Properties of Dielectric Materials	
Current Carrying Capabilities and Current Rating Nomograph	
IPC Specification List	
COMPUTER AIDED DESIGN (CAD) INFORMATION	23
Design/Data Transfer Information	
GLOSSARY	24
REQUEST FOR QUOTE WORKSHEET.....	25-26

BENEFITS OF FLEXIBLE CIRCUITRY

1. A SOLUTION TO A PACKAGING PROBLEM.

- Flexible circuits allow unique designs which solve interconnection problems.
- The ability to fold and form flex circuits enables a package size reduction.
- Flex circuits make installation and repair practical and cost effective.

2. REDUCE ASSEMBLY COSTS.

- Flex circuits can be tested prior to assembly of components.
- Reduction of connectors and solder joints lower costs.

3. REPLACEMENT FOR A CIRCUIT BOARD AND WIRES.

- Flexible circuits simplify system design.
- Flex reduces the number of levels of interconnection required in an electronic package.
- Flexible circuits eliminate human error common in wire assemblies as routing is determined by artwork and repeatability is guaranteed.

4. REDUCE WEIGHT AND SPACE.

- Considerable weight reduction is a benefit over wire harnesses, and rigid assemblies.
- Thickness can be as thin as .004 inches (.10mm) in total.

5. DYNAMIC FLEXING.

- The thinness of the material makes flexible circuits the best candidate for flexible applications up to millions of flexures.

6. THERMAL MANAGEMENT/ HIGH TEMPERATURE APPLICATIONS.

- Flex circuits dissipate heat at a better rate than any other dielectric materials.

7. AESTHETICS.

- Flex circuits improve the internal appearance of an electronic package, which can have an influence on the decision making process of prospective users of the product.

Flexibility to meet customers needs

FOR STANDARD MANUFACTURING CAPABILITIES

(inquire within about nonstandard sizes)

CIRCUIT CONSTRUCTIONS:

SINGLE-SIDED

DOUBLE-SIDED

MULTI-LAYER

RIGID FLEX

SHIELDING:

COPPER

TATSUTA, SILVER

STANDARD CIRCUIT SIZES:

(Longer available, considered MAXI-Flex®)

SINGLE-SIDED:

up to 22" by 28"
(558.8mm by 711.2mm)

DOUBLE-SIDED:

up to 16" by 22"
(406.4mm by 588.8mm)

MAXI-FLEX®:

up to 20" by 40' plus
(508mm by Length)

MULTI-LAYER:

12" by 24"
(304.8mm by 609.6mm)

RIGID FLEX:

6-8 Layers standard construction
(depending on complexity and design)

HOLE SIZE:

NON-PLATED (Standard Processing)

THRU HOLES:

.005" (.125mm) min. drilled hole size.
Tolerance +/- .0015" (.038mm)

PLATED THRU HOLE:

.005" (.125mm) min. drilled hole size.
Tolerance +.003" (.076mm),
-.005" (.125mm)

(Smaller holes can be manufactured, contact
All Flex Sales)

LINE WIDTH AND SPACING:

.004" (.1mm) MINIMUM LINE

.004" (.1mm) MINIMUM SPACING

(Finer lines can be manufactured, contact
All Flex Sales.)

CIRCUIT/BLANKING CONSIDERATIONS:

SOFT TOOLING:

Outline dimensions
+/- .005" (.125mm)

Radius of inside corners minimum of
.023" (.584mm)

Edge insulation
.010" min (.254mm)

HARD TOOLING:

Outline dimensions
+/- .001" (.0254mm)

Edge insulation
.006" min (.152mm)

LASER CUT:

Outline dimensions
+/- .003" (.25mm)

Edge insulation
.004" (.102mm)

DRILL POSITION:

Tolerance of +/- .003" (.076mm)

ZIF END TOLERANCE:

+/- .002" (.0508mm) with CpK>2.0

ADDED VALUE CAPABILITIES

- **AUTOMATED MIXED FORM FACTOR ASSEMBLY**
- **SURFACE MOUNT COMPONENTS**
Down to 0201
Thru hole assembly
(see more on page 10)
- **PLACEMENT ACCURACY TO .001"**
- **RoHS COMPLIANT ASSEMBLY**
- **PRECISION STENCILING**
- **HEAT SINKS**
- **ELECTRICAL TESTING**
- **FOLDING FORMING**

Circuit Design and Engineering
support will **ASSIST YOU**

STANDARD MATERIALS

BASE MATERIALS:

Polyimide:

.0005" to .005"
(.012mm - .127mm)

Polyester:

.002" to .010"
(.050mm - .254mm)

Adhesiveless Materials:

Copper thickness
.5 oz. to 4 oz.

Flame Retardant:

Laminates and Coverlay

Other Materials Upon Request

BASE COPPER:

.5 oz. - .0007" (.018mm) thick copper
1 oz. - .0014" (.036mm) thick copper
2 oz. - .0028" (.071mm) thick copper
3 oz. - .0042" (.107mm) thick copper
4 oz. - .0056" (.142mm) thick copper
5 oz. - .0070" (.178mm) thick copper
6 oz. - .0084" (.213mm) thick copper
7 oz. - .0098" (.249mm) thick copper

Thicker coppers are available (call for information). See current carrying chart on page 20.

SOLDER MASK:

Polyimide coverlay:

.0005" to .005"
(.012mm - .127mm)

Polyester coverlay:

.0015" to .003"
(.038mm - .076mm)

Photo-imageable covercoat:

LPI - Liquid Photo Imagable - for high density applications.

SURFACE FINISH:

Hot Air Solder Level (HASL)

RoHS Compliant and Tin Lead

Tin Plating (RoHS Compliant)

Electroless and electrolytic

Silver (RoHS Compliant)

Immersion

Hard Gold over Nickel

(RoHS Compliant)

(Typically used for contacts)

Soft Gold over Nickel

(RoHS Compliant)

(Electrolytic - sometimes used for bonding gold wire to the gold layer)

ENIG (Electroless Nickel

Immersion Gold) (RoHS

Compliant)

(Electroless - sometimes used for bonding aluminum wire to the nickel under the gold)

Organic Coating

OSP (RoHS Compliant)

RIGIDIZERS/STIFFENERS:

FR4-drilled, routed, or scored

Aluminum

Polyimide

Polyester

Stainless Steel

CERTIFICATIONS:

ISO 9001: 2008 Certified

AS9100 Certified

MIL-P-50884E Qualified

RoHS Compliant

IPC Member: Product is manufactured in accordance with the requirements of IPC-6013B Classes 1, 2, 3

ITAR Registered


JCP Certified

UL Recognized: for single and double sided constructions with individual polyimide layers up to 5 mil, including several surface finishes. (File # E161240)

Flexibility to meet customers needs

SINGLE-SIDED & DOUBLE-SIDED CIRCUIT CONSTRUCTION

SINGLE-SIDED FLEXIBLE CIRCUITS




Single-sided flexible circuits consist of a single conductive layer on a flexible dielectric film (see diagram below).

SINGLE-SIDED FEATURES:

- Very thin construction .004"-.008" (.10mm-.20mm)
- 1 Conductive layer.
- Reverse bared or back bared pads, provide access from both sides of the part.
- Supported and unsupported finger areas.

WHEN TO USE SINGLE-SIDED FLEX:


- Dynamic flexing applications
- Unusual folding and forming applications.
- Installation/service applications/repair.
- Limitations on space / thickness
- Installation / Service flexing




(refer to standard materials page for material availability)

A UNIQUE TYPE OF SINGLE SIDED CIRCUIT SCULPTURED FLEX CIRCUITS

Sculptured flex circuits have variable copper thicknesses within the part. Thin copper is used for the flexible regions, and thicker copper is used at the interconnection point. Sculptured flex circuits provide bare metal connections and are a highly reliable alternative to mechanically crimped contact pins.



DOUBLE-SIDED FLEXIBLE CIRCUITS




Double-sided flexible circuits consist of two conductive layers normally connected with a plated through-hole (see diagram below).

DOUBLE-SIDED FEATURES:

- Component assembly available on both sides.
- Two conductive layers.

WHEN TO USE DOUBLE-SIDED FLEX:

- Required when circuit density and layout can not be routed on a single layer.
- Ground and power plane applications.
- Used for shielding applications.
- Dense surface mount assembly.




(refer to standard materials page for material availability)

MULTI-LAYER & RIGID-FLEX CIRCUIT CONSTRUCTION

MULTI-LAYER CONSTRUCTION CIRCUITS


- Controlled impedance and shielding possible.



WHEN TO USE MULTI-LAYER FLEX:

- Required when circuit density and layout can not be routed on a single or double layer.


- Ground and power plane applications.
- Used for shielding applications.
- Dense surface mount assembly.
- Increased circuit density.
- EMI/RFI shielding.
- Controlled impedance with shielding.



(refer to standard materials page for material availability)

RIGID-FLEX CIRCUITS

Rigid-Flex circuits are characterized by having conductors on both the flexible and rigid layers of the circuit. Plated thru holes extend between the flexible and rigid sections and electrically connect multiple conductor layers. Rigid-flex circuits are often used when components are mounted on both sides of the rigid section. This circuit construction is known as a Type 4 circuit as defined by IPC 6013 and should be distinguished from a flexible circuit with a rigid stiffener attached.



Inquire Within

Flexibility to meet customers needs



54"L Maxi-Flex® Circuit

All Flex is one of the few companies in the world that manufactures flexible circuits in exceptional lengths over 24".

All Flex has trade marked our special flex circuit offering that allows an application to be produced at larger than normal sizes. MAXI-FLEX® is a circuit that is normally found on one or two conductive layers longer than 24" in length. Additional layers may be added.

MAXI-FLEX®

Custom Designed Copper Flexible Circuits in exceptionally long lengths up to 40'+.

- Sizes from 2' to 40'+ by 20" max
- Single-sided, double-sided, multi-layer
- Plated through holes
- Ideal for large systems and unmanned systems
- Permits tight bends
- Eliminates bulky cabling
- For use in military and aerospace applications
- Standard conductor pitch down to 0.030" (0.76mm) (finer pitch available, call ALL FLEX sales for more information)
- Shielding possible to provide EMI/RFI protection
- Controlled impedance design available
- Light Weight, dense packaging solutions
- Replacement for wire harnesses

- Custom termination design for use with:
 - High density circular connectors
 - D subminiature connectors
 - Surface mount connectors & components
 - Pin and socket connectors
 - Leaded components
 - Edge card and zif connectors
 - Crimp-on/displacement pins and connectors

MAXI-FLEX® circuits are designed for your specific application with signal, power and shielding layers in one complete interconnect package.

(IMPORTANT: DUE TO MATERIAL AVAILABILITY in these lengths, contact All Flex staff for further information on standard MAXI-FLEX® construction.)

ALL FLEX HAS THE UNIQUE CAPABILITY TO MANUFACTURE HEATERS AND ASSEMBLE COMPONENTS

All Flex can design, fabricate, and reverse engineer flexible heaters to meet customer's exact requirements. Flexible polyimide and silicone rubber heaters and heater component assemblies are fabricated with a variety of metal alloys to deliver custom solutions for heating capacity, watt density, and other application specific customer needs. Typical lead times 2 – 3 weeks upon customer approval.


FLEXIBLE HEATER FEATURES:

- Temperatures up to:
 - 120°C Polyimide
 - 232°C Silicone Rubber
- Circuit size up to 22" x 30" (558mm x 762mm)
- Resistant to most chemicals
- Engineered to meet specified output
- Flexible Heaters can be supplied as thin as .004"
- Component and connector assembly
- Soldered wire assembly for connections
- Epoxy reinforced soldered wires
- Bifilar Heater – A heater that consists of two parallel traces of differing resistance. User can heat one, the other, or both traces essentially making three heaters in one. Bifilar heaters can be advantageous if the user wants to keep control logic to a minimum.

OTHER CONSIDERATIONS/ADD ONS:

- Thermistor assembly
- Heater can be built with multiple heating zones
- Quick turn available
- Any volume quantities
- Assembly expertise
- Epoxy coated solder joints provide strain relief and insulation and environmental protection
- UL Recognized
 - (File #E338387)
 - (Category KSOT2)

- PSA – Pressure Sensitive Adhesive can be applied to either surface for a peel and stick application
- Heat spreaders of aluminum can be applied to the heater to reduce the incidence of hot spots
- Designs can be manufactured to reduce or eliminate heat in certain positions of the heater
- Heaters can be designed/manufactured into virtually any size or shape, with or without clearance holes
- All heaters are custom designed and manufactured to customer specifications
- Special marking of part number or image



Heaters can be designed and manufactured into virtually any size and shape.

All Flex can
REVERSE ENGINEER
to meet exact requirements

Flexibility to meet customers needs

CUSTOM HEATERS

POLYIMIDE & SILICONE RUBBER


HYBRID

All Flex engineering will work closely with you to ensure the proper design and layout. The following are typical characteristics and parameters of our heater circuit products.

DESIGN PARAMETERS

CHARACTERISTICS	TYPICAL PARAMETERS - POLYIMIDE	TYPICAL PARAMETERS - SILICONE
	<i>* Note - these are standard parameters inquire within for requirements beyond this range</i>	
Size Range*	Less than ½" square up to 10"x22"	Less than ½" square up to 24"x30"
Temperature Range	Up to 248° F (120° C)	Up to 450° F (232° C)
Resistance Range	Up to 250 Ω per sq in	Up to 250 Ω per sq in
Metal Thickness Range*	.0005" - .002"	.0005" - .002"
Total Thickness Range*	.0045" - .01"	.03" - .06"
Dielectric Range/ Insulation Resistance	4000-5000 V/mil	400-600 V/mil
Example Power Densities	2.5 W/in ² -low end, 5 W/in ² -all purpose, 10 W/in ² -rapid warmup	2.5 W/in ² -low end, 5 W/in ² -all purpose, 10 W/in ² -rapid warmup
Resistance Tolerance*	+/- 10%	+/- 10%
Maximum Voltage	Up to 115 V	Up to 220 V
Standard Coverlay Thickness	.001", .002", .003" and .005"	.015"
Leads (if required)	Length/AWG/Coating	Length/AWG/Coating

Multi-zone heaters give customers full flexibility in managing their processes while offering uniform and easy to install elements. Available in both polyimide and silicone rubber.



HYBRID HEATERS

Now your single or double sided circuit assembly can have built-in heaters.

All Flex can take your electronic circuitry requirements and your heat requirements and create a hybrid product. Typically the heater function is on one side of the base film and the electronics function is on the opposite side. By combining a copper layer for the electronics with a layer of resistive metal for the heater, a hybrid circuit can be designed. Top to bottom electrical connection can be done with plated thru holes. All Flex has unique process and materials that can accommodate even the most challenging hybrid requirements.

ADVANTAGES OF A HYBRID HEATER

- Thinner overall profile
- Reduces overall assembly weight
- More robust functionality
- Lower over all costs

HEATER APPLICATIONS

MEDICAL


All Flex heaters provide precise heating and thermal control in applications where thermal management is extremely important.

All Flex Understands:

- Medical quality requirements
- FDA traceability expectations
- Medical device qualification procedures
- Clean room/precision assembly needs of medical customers
- Medical device product development cycles
- Small and medium volume delivery needs

Some Applications:

- Incubator
- Operating room equipment
- Surgical tools
- Defibrillator
- Dialysis equipment
- Blood analysis equipment
- Medical instrumentation and laboratory equipment



Breath Analyzer

AERONAUTICS/AEROSPACE

All Flex is AS9100, ISO 9001:2008 Certified, ITAR Registered, Mil-P-50884E Compliant.



Heating technology is used extensively in the Aeronautics and Aerospace industry due to the temperature extremes and the need for reduced weight and compact electronics. All Flex heaters help to maintain high reliability of electrical components by limiting exposure to high degrees of thermal contraction/expansion cycles.

All Flex Heaters also keep non-electrical components at constant temperatures for both functional and convenience purposes.

The typical application for heaters in this industry is not to heat devices to high temperatures, but to keep devices from getting cold. Our technology enables us to fabricate heaters that remain flexible and compliant at -55 degrees C (-67 degrees F) while heating to slightly above freezing.

Some Applications:

- Helicopter controls
- Aircraft controls
- De-icing systems
- Satellite hardware
- Cockpit systems



Lab Analysis Heater

MILITARY/DEFENSE

All Flex is AS9100, ISO 9001:2008 Certified, ITAR Registered, Mil-P-50884E Compliant.

All Flex Heaters provide an excellent solution for high performance, densely packed electronics where space is a premium yet heating of components are needed. Numerous All Flex Flexible Circuits are used by prime contractors, NASA, developmental laboratories, and government agencies.

Some Applications:

- Aircraft equipment
- Night vision
- Sighting systems
- Ruggedized computers

Flexibility to meet customers needs

HEATER APPLICATIONS & STOCK HEATERS

OUTDOOR ELECTRONICS

Devices and equipment that are exposed to cold temperatures creates design challenges for manufacturers. Typical thermal cycling introduces molecular expansion issues that can impact electronics, cause mechanical wear, introduce moisture variation, restrict moving parts, and other functional and operational problems.

Some Applications:

- Automated Teller Machines
- Outdoor LED and Canister Lighting
- Outdoor LCD Screen
- Ruggedized electronic and computer devices made to operate in extreme weather conditions

GENERAL & INDUSTRIAL ELECTRONICS

All Flex Heaters are used in a wide variety of electronic applications to assist in the performance of our customers' end products.

Some Applications:

- Food service equipment
- Storage tanks
- Battery heaters to enhance battery performance
- Photo processing
- Outdoor antenna
- Hand-held scanners

STOCK HEATERS:

(for production products or test/evaluation)


Generally our customers have unique design requirements that necessitate customization for their particular device or application, however one of our standard heaters may meet your needs. All Flex offers standard, non-custom flexible heaters. These heaters are classified as either Stocked or Build to Order (BTO) and are available without a tooling or set-up charge.

Select size/shape, resistance, or watt density (watts per square inch) to determine if a particular stock product meets your needs then assess the additional options below that may be required.

Stocked heaters options:

- Each stocked heater is available with a pressure sensitive back-piece cut to the same size as the heater.
- Aluminum heat-dissipation shield, cut to the same size as the heater.
- Custom marking is available as specified and desired by the customer.
- The addition of wires and associated wire characteristics
- UL Recognition

Visit: WWW.ALLFLEXHEATERS.COM for a complete listing of all standard stock heaters, technical detail, lead times, pricing, option pricing, etc.



All Flex heaters can be supplied with PSA (Pressure Sensitive Adhesive) on the back of the heater with a release liner for easy peel and stick, the PSA makes installation quick and easy.

Our Vision...
is to be your
PREFERRED SUPPLIER
for flex...

ALL FLEX ADDS VALUE

All Flex has the capability to quickly design, manufacture and deliver in volumes from prototype to production. All Flex has manufactured hundreds of designs for the military, medical and industrial markets.




HAND ASSEMBLY

- Operators certified to J-STD
- Lead and lead free capability
- ESD controls

AUTOMATED PICK AND PLACE CAPABILITY PROVIDES COMPLEX ASSEMBLY COMBINATIONS INCLUDING:

- Surface mount components down to 0201
- Precise vision system allows placement accuracy to .001"
- Fine pitch capability to .5mm pitch
- Leaded devices
- Tactile domes
- Staked terminals
- Unlimited component configurations
- RoHS Compliant assembly
- Virtually all SMT components including discretes, SOICs, PLCCs, QPPs, & BGA's
- Auto fiducial correction



AUTOMATED ASSEMBLY

- **Solder Screener**
Automated screening of solder onto arrays/panels using solder stencil
Lead and lead free capability
- **Selective Soldering**
Automated ability to solder leads on through hole connector
Lead and lead free capability

OTHER ALL FLEX ADDED VALUE CAPABILITIES

- Thru hole assembly
- Flexible circuit folding and forming (see page 13)
- Electrical testing
- Heat Sinks
- Nomenclature Screening
- Stiffener placement
- Design and manufacturing support – concept to completion

CIRCUIT TESTING CAPABILITY

- | | |
|------------------------------|-----------------|
| • Solderability | • Microsections |
| • Ionic contamination | • Continuity |
| • Dimensional tolerance | • Inductance |
| • Thermal testing | • Capacitance |
| • Dielectric net-to-net | • Resistance |
| • Insulation resistance (IR) | • Impedance |

POTTED CIRCUITS

connector securely adhered with potting compound to perform in rugged applications where vibration is typical



Flexibility to meet customers needs

SURFACE DIELECTRICS OPTIONS

Surface dielectrics are applied to the outside layers of the circuit to insulate the copper conductors.

Following are types of surface dielectrics used at All Flex.

POLYIMIDE/POLYESTER COVERLAY

These materials are normally produced with a drilling process. Limitations to the drilling process enable production of round and oval holes, leaving the inability to have square openings, dense features or any unique shape other than round or oval. Both polyester and polyimide coverlay can be punched or blanked in lieu of the drilling process and is normally done for large coverlay openings.

VIA HOLE:


Covered with coverlay

COMPONENT HOLE:

.005" (.127mm) minimum larger than the copper pad

FEATURE DEFINITION:

.008" (.20mm) minimum




Note: Coverlay openings can be individual bared pads or group bared pads depending on area available.

Note: Group bared pads are used when there is not enough room to have individual openings.

LIQUID PHOTOIMAGEABLE SOLDERMASK

Liquid Photoimageable Soldermask (LPI) is produced by a photo controlled process and used for tight pad spaces. This process enables unique openings to be applied anywhere on the circuit. LPI is usually not used with 2oz. copper or above due to the thickness of the copper as it may not conform around the area of some copper features.



VIA HOLE:

Covered with soldermask

LPI Opening = .006" minimum larger than pad with .004" minimum web spacing

SURFACE DIELECTRICS OPTIONS	
LIQUID PHOTOIMAGEABLE SOLDERMASK (LPI)	
ADVANTAGES	DISADVANTAGES
Higher pattern resolution	Not recommended for dynamic flex applications
Eliminates punching and drilling of access holes	Less robust mechanically
POLYIMIDE/POLYESTER COVERLAYER FILMS	
ADVANTAGES	DISADVANTAGES
Excellent dynamic flexibility	Adhesive may be susceptible to cleaning solvents
Pinhole free	Requires pre-cutting and/or pre-punching
Highest dielectric strength	Susceptible to misregistration/ dimensional change

DESIGN GUIDELINES: CONDUCTOR PAD DESIGN AND FILLETING

This section of our guide addresses rules specifically pertaining to conductor and pad design recommendations. Due to

the flexible nature of the material during both manufacturing and application use, the following information is


recommended to produce the highest yielding and best functioning flexible circuit.

CONDUCTOR PAD DESIGN:

Pads should have tie-downs (also called anchoring spurs or rabbit ears). Tie-downs are captured by the coverlay to anchor the copper to prevent separation between the copper and the base material during assembly.


FILLETING:

All pads, on both through-hole and surface mount pads, should be filleted to reduce stress points. This helps eliminate breaking during flexing.



CALCULATING PAD SIZE:

Recommended pad size is dependent on the component pad requirement that is specific to your application.




FORMULA:

$$\begin{array}{rclcl} \text{HOLE SIZE (FINISHED)} & + & \text{CUSTOMER REQUIRED TOLERANCES} & + & \text{ALL FLEX TOLERANCE} & = & \text{PAD SIZE REQUIRED} \\ .030" (.76\text{mm}) & & \pm .003" (.07\text{mm}) & & .020" (.50\text{mm}) & & .053" (1.34\text{mm}) \end{array}$$

Flexibility to meet customers needs


DESIGN GUIDELINES:

TO INCORPORATE IN BENDING AND FOLDING DESIGNS




RADIUSED TRACES help to alleviate breaking during folding and bending.

I-BEAM constructions occur when the conductors on both layers lie directly on top of each other, increasing the stiffness of the circuit through fold areas. A better alternative is to stagger conductors, alternating their location to retain the maximum flexibility of the circuit.




STAGGERED CONDUCTORS
Preferred Construction



I-BEAM CONSTRUCTION
Not Recommended


FOLD LINES may be designated by "tick" marks which may be either in the copper layers or silkscreen layers. These features aid in bending and designating bend locations.



CIRCUIT TRACE WIDTH should not change in bend areas and the transition should be at least .030" (.76mm) from the fold line.

BEND RADIUS of a flex should be approximately 10 times the material thickness and at least .050" away from the plated through hole.

$$r=10 \times T$$




BUTTON PLATING/PADS

ONLY PLATING is a process that allows for the plated through holes to maintain their connection while the traces are not plated, allowing the circuit to have increased flexibility.

SHIELDING

If your application requires limits in electromagnetic and/or electrostatic interference, shielding may be required. Shields are material around a conductor or group of conductors that limit these factors.



SOLID COPPER:

Solid Copper is the most common method of shielding. Solid copper shields increase the rigidity of the circuit, and should be included in thickness to bend radius ratios. Copper shield can be put on one or both sides of the circuit. Solid copper can also cover selective conductors.

CROSSHATCHED COPPER:

Crosshatching is an artwork design that relieves much of the copper shield areas by the use of a pattern. Crosshatching helps the circuit to retain its flexibility and can be put on one or both sides. Crosshatch shielding can also cover selective conductors.


Note: Additional shielding options exist, such as shielding between circuit conductor. Contact All Flex Staff for further details.

CONDUCTIVE SILVER:

Conductive silver can be substituted for the copper for shielding purposes in some applications. Silver shielding is not recommended for a dynamic flexing application due to its brittle characteristic, and may be prone to cracking in severe bending applications. Silver can be a solid or crosshatched shield and can be put on one or both sides of the circuit. It can also cover selected conductors only.

CONDUCTIVE SHIELDING FILM:

Metalized film with a conductive adhesive coating is thermally bonded to flexible circuitry. Selective openings in the coverlay film allow the conductive adhesive to electrically contact the flex circuit. This creates a shielding layer by the contact between the metalized film and the ground traces.




Flexibility to meet customers needs

SHIELDING


CHARACTERISTIC IMPEDANCE:

Controlled impedance is important in high speed digital circuitry to avoid signal reflectance and power loss. The impedance of a flexible printed circuit depends on dielectric constant of the base material, conductor width, conductor thickness and dielectric thickness.

STRIPLINE



SINGLE ENDED MICROSTRIP



FLEXIBLE POLYIMIDE CIRCUIT – IMPEDANCE REFERENCE CHART

SINGLE ENDED MICROSTRIP				
MATERIAL THICKNESS INCLUDING ADHESIVE	TRACE WIDTH FOR 50 OHMS IMPEDANCE 1/2 OZ COPPER	TRACE WIDTH FOR 50 OHMS IMPEDANCE 1 OZ COPPER	TRACE WIDTH FOR 75 OHMS IMPEDANCE 1/2 OZ COPPER	TRACE WIDTH FOR 75 OHMS IMPEDANCE 1 OZ COPPER
0.002	0.0036	0.0032	0.0015	>.001
0.003	0.0057	0.0053	0.0025	0.0013
0.004	0.0078	0.0074	0.0035	0.0028
0.005	0.0102	0.0096	0.0050	0.0041
0.006	0.0122	0.0117	0.0060	0.0050
0.007	0.0144	0.0139	0.0070	0.0060
0.008	0.0166	0.0161	0.0080	0.0068
0.009	0.0189	0.0184	0.0088	0.0085
0.010	0.0211	0.0206	0.0105	0.0095

All calculations assume .002 thick coverlay, 3.4 dielectric constant and 50% trace/ 50% space on differential pairs

RIGIDIZERS/STIFFENERS

Often circuit applications require support in areas where connectors or other components are applied. Here are the recommended types of guidelines for stiffeners.

FR4/G10 STIFFENERS:


- Come in a variety of thicknesses such as .010" (.25mm), .020" (.50mm), .031" (.78mm), .047" (1.19mm) and .062" (1.57mm).
- Can be bonded to a flex circuit using a pressure sensitive adhesive or a thermoset adhesive.
- Are normally used to give added rigidity under a component area.
- Used as a carrier panel for automated assembly processing.
- Hole size in the stiffener should be .015" (.38mm) larger than the circuit thru-hole to allow for registration tolerances.

POLYIMIDE OR POLYESTER STIFFENERS:


- Come in a variety of thicknesses from .001" (.02mm) up to .015" (.38mm) or higher.
- Can be bonded to a flex circuit using a pressure sensitive adhesive or a thermal set adhesive.
- Can be used to give added thickness under conductors to meet ZIF connector requirements. .
- Can be used to give added strength in high wear areas.
- Can be blanked at the same time as the circuit outline to meet tight tolerance requirements.

LOCATION OF STIFFENER:

Stiffener and coverlay termination points should overlap a minimum of .030" (.76mm) to avoid stress points. Eliminating stress points reduce the chance of traces breaking.



(This is the PREFERRED METHOD because there is not common ending point of the coverlay and stiffener.)



(This form is NOT RECOMMENDED because it allows potential stress and cracking points where the coverlay and stiffener end at a common edge.)

Flexibility to meet customers needs


TERMINATION METHODS

There are many ways to terminate a flexible circuit. Following are common methods for consideration.

ZIF CONNECTORS:


Zero Insertion Force connectors are a popular method to terminate a flexible circuit. ZIF connector fingers on the flex circuit insert into a mating connector. The ZIF end inserted into the connector are usually located on a rigid board.

Blank tolerance $\pm .002"$



THRU-HOLE OR SURFACE MOUNT CONNECTORS:

These are the traditionally used connectors in today's circuit boards.




CRIMPED CONTACTS AND DISPLACEMENT CONNECTORS:

- Contacts crimp through the dielectric material into the copper conductor.
- Contacts are available for .100" (2.54mm) or .050" (1.27mm) centers.
- Centerline housings are also available to encapsulate the contact.

SCULPTURED (UNSUPPORTED) TRACES AND POWER FLEX:

- Thicker copper allows flexible circuit designs to carry higher current through small spaces.
- Selective etching allows a reduction in copper thickness in selective areas for increased flexibility.
- Copper thickness from 0.003" (0.076mm) to 0.010" (0.254mm)



Sculptured (unsupported) Traces

ADDITIONAL CUSTOM TERMINATION OPTIONS:

- High density circular connectors
- D subminiature connectors
- Pin and socket connectors
- Leaded components

RECOMMENDED SUPPLIERS LIST FOR FLEXIBLE CIRCUIT CONNECTORS:

1. Heilind Electronics (866) 286-0322
www.Heilind.com
2. Samtec (800) 726-8329
www.Samtec.com
3. Digi-Key (800) 344-4539
www.digikey.com
4. New Advantage Corporation (727) 576-0550
www.newadvvg.com

REQUEST
quotes, samples,
and design consults online
www.allflexinc.com

ADDITIONAL TECHNICAL INFORMATION

IPC INFORMATION

The following list contains the IPC specifications that you can reference in regards to specific materials, design, performance and assembly questions.

MATERIALS

- IPC-4202**
Flexible Base Dielectrics
- IPC-4203**
Adhesive Coated Dielectric Films
- IPC-4204**
Flexible Metal-Clad Dielectrics
- IPC-4101**
Rigid PC Board Materials

DESIGN

- IPC-FC-2221**
Generic Standard on Printed Circuit board Design
- IPC-FC-2222**
Rigid Circuit Boards
- IPC-FC-2223**
Flexible Circuits

PERFORMANCE

- IPC-6011**
Generic Performance Specifications for Printed Circuits
- IPC-6012**
Qualification and Performance for Rigid Circuit Boards
- IPC-6013**
Qualification and Performance for Flexible Circuits

CIRCUITS AND ASSEMBLY (QUALITY GUIDELINES)

- IPC-A-600**
Acceptability of Printed Boards
- IPC-A-610**
Acceptability of Printed Board Assemblies
- IPC/EIA J-STD001**
Requirements for Soldered Electrical & Electronic Assemblies

Visit the IPC web site @ www.ipc.org

ALL FLEX is an active, award winning
IPC Member, holding chair positions on the
flexible circuit materials committee.

Flexibility to meet customers needs

ADDITIONAL TECHNICAL INFORMATION

TYPICAL PROPERTIES OF DIELECTRIC MATERIAL FOR FLEXIBLE PRINTED CIRCUITRY


PROPERTY (TYPICAL)	UNITS	POLYIMIDE	POLYIMIDE (Adhesiveless)	POLYESTER
REPRESENTATIVE TRADE NAME		KAPTON	KAPTON	MYLAR
PHYSICAL				
Thickness Range	mil	0.5 to 5	1-6	2-5
Tensile Strength (@25° C)	psi	25,000	50,000	20,000 to 35,000
Break Elongation	%	70	50	60 to 165
Tensile Modulus (@25° C)	100,000 psi	4.3	.7	5
Tear Initiation Strength	lb/in	1000	700-1200	1000 to 1500
Tear Propagation Strength	g/mil	8	20	12 to 25
CHEMICAL				
Resistance to:				
Strong Acids		Good	Good	Good
Strong Alkalis		Poor	Good	Poor
Grease and Oil		Good	Good	Good
Organic Solvents		Good	Good	Good
Water		Good	Good	Good
Sunlight		Good	Good	Fair
Fungus		Non-nutrient	Non-nutrient	Non-nutrient
Water Absorption (ASTM D570)	% (24 hours)	2.9	.8	<0.8
THERMAL				
Service Temperature (min/ max)	degree C	-125/+200	-125/+200	-60/+105
Coefficient of Thermal Expansion (@22° C)	PPM/degree C	20	20	27
Change in Linear Dimensions (100° C, 30 min)	%	<0.3	0.04-0.02	<0.5
ELECTRICAL				
DIELECTRIC CONSTANT (ASTM D150) 1MHz		3.4	3.4	3
DISSIPATION FACTOR (ASTM D150) 1MHz		0.01	.003	0.018
DIELECTRIC STRENGTH (ASTM D149) @ 1 mil thickness Volume Resistivity (ASTM D257)	V/mil ohm-cm	6000 1.0E+16	6000 1.0E+16	3400 1.0E+16

CURRENT CARRYING CAPABILITIES:

COPPER WEIGHT								
AMPS	1/2 OZ. (.0007")	1 OZ. (.0014")	2 OZ. (.0028")	3 OZ. (.0042")	4 OZ. (.0056")	5 OZ. (.007")	6 OZ. (.0084")	8 OZ. (.0112")
CONDUCTOR WIDTH IN INCHES								
0.5	.013"	.008"	N/A	N/A	N/A	N/A	N/A	N/A
1.0	.028"	.017"	.013"	N/A	N/A	N/A	N/A	N/A
1.5	.040"	.027"	.020"	N/A	.012"	.005"	.003"	N/A
2.0	.053"	.040"	.030"	.0235"	.020"	.018"	.016"	.013"
2.5	.080"	.060"	.042"	.0325"	.0285"	.024"	.023"	.018"
3.0	.100"	.083"	.057"	.045"	.0387"	.035"	.030"	.024"
4.0	.160"	.120"	.088"	.066"	.055"	.048"	.043"	.037"
5.0	.225"	.158"	.118"	.09"	.074"	.065"	.059"	.048"
6.0	.285" (off chart)	.195"	.153"	.117"	.094"	.082"	.074"	.062"
7.0	N/A (off chart)	.250"	.187"	.145"	.124"	.105"	.0905"	.075"
8.0	N/A (off chart)	.307"	.232"	.180"	.1485"	.130"	.122"	.095"

This chart gives recommendations for width of conductor needed to carry current on different copper thicknesses.

CURRENT RATING NOMOGRAPH:



Relation between current rating and size of a single conductor for constant temperature rise in air. Conductor dimensions above the line "WIDTH/THICKNESS = 5" are preferred for ease of manufacture.

Flexibility to meet customers needs

COMPUTER AIDED DESIGN (CAD) INFORMATION

DATA FORMATS:

RS 274X (Gerber)
PDF
dwg
IGES
DXF

TO COMMUNICATE:

BY E-MAIL:

General Mailbox:
information@allflexinc.com

Call ALL FLEX:

engineering toll free at
877-663-7162

README FILE SHOULD:

- Contain your company name
- Contain a list of included files and their functions
- Contain your company contact and phone number

INFORMATION CAN BE RECEIVED IN A NUMBER OF WAYS:

- Mechanical print/sketches
- Schematic drawings
- Component Specifications
- Existing Artwork to be Scanned
- Fax (507) 663-1070
- E-mail (information@allflexinc.com)
- Secure FTP: <ftp://mail.allflexinc.com>
(contact us for password)
- Request a quote: rfq@allflexinc.com

DESIGN: ALL FLEX OFFERS THE FOLLOWING DESIGN OPTIONS FOR OUR CUSTOMERS.

- Reverse engineering of existing parts, design from concept, or design from schematic.
- Gerber creation: Contact ALL FLEX sales for more information.
- Critique of customers design for flexibility and manufacturability.

We provide
QUOTES in 24 hours

GLOSSARY

ANNULAR RING

That portion of conductive material completely surrounding a hole.

ARTWORK

An accurately-scaled configuration that is used to produce the "Artwork Master" or "Production Master."

BACK-BARED LAND

A land in flexible printed wiring that has a portion of the side normally bonded to the base dielectric material exposed by a clearance hole.

BASE FILM

The film that is the base material for the flexible printed wiring board and on the surface of which the conductive pattern can be formed. When the heat resistance is required, polyimide film is mostly used, and polyester film is usually used when the heat resistance is not required.

BLANKING

Cutting a sheet of material into pieces to the specified outline.

CHARACTERISTIC IMPEDANCE

The resistance of a parallel conductor structure to the flow of alternating current (AC), usually applied to high speed circuits, and normally consisting of a constant value over a wide range of frequencies.

COPPER WEIGHT

The mass of copper per unit area for a foil, typically expressed in ounces per square foot or grams per square centimeters (these units are not equivalent).

COVERLAY

The layer of insulating film and adhesive that is applied totally or partially over a conductive pattern on the outer surfaces of a printed board.

DELAMINATION

A separation between plies within a base material, between a base material and a conductive foil, or any other planar separation within a printed board.

DIELECTRIC

A material with a high resistance to the flow of direct current, and which is capable of being polarized by an electrical field.

ETCHING

The chemical, or chemical and electrolytic, removal of unwanted portions of conductive or resistive material.

FIDUCIAL

A printed board feature (or features) that is (are) created in the same process as the conductive pattern and that provides a common measurable point for component mounting with respect to a land pattern or land patterns.

FLEXIBLE HEATER

Custom designed polyimide and silicone rubber heaters fabricated with a variety of resistive alloys for custom heating solutions.

GERBER DATA

A type of data that consists of aperture selection and operation commands and dimensions in X- and Y-coordinates. (The data is generally used to direct a photoplotter in generating photoplotted artwork.)

MOISTURE ABSORPTION

The amount of water the base material will absorb.

PANEL PLATING

The plating of an entire surface of a panel including holes.

PHOTOIMAGED SOLDERMASK

Produced by a photo controlled process and used for tight pad spaces. This process enables unique openings to be applied anywhere on the circuit.

RESISTIVE METAL

Copper alloy or other metals selected for their resistive properties to design flexible heaters.

ROLLED ANNEALED

Copper rolled foil to a predetermined thickness and then treated through an annealing process.

STIFFENER BOARD

A material fastened to the surface of a printed board to increase its mechanical strength.

VIA

A plated-through hole that is used as an interlayer connection, but in which there is no intention to insert a component lead or other reinforcing material.

Source: "Terms and Definitions for Interconnecting and Packaging Electronic Circuits" IPC-T-50

See www.ALLFLEXINC.com/EngineeringTools/Glossary for a complete listing of flexible circuitry terms.

Flexibility to meet customers needs

REQUEST FOR QUOTE (RFQ) GUIDELINE

FLEXIBLE CIRCUITS

Email To: information@allflexinc.com
or Fax To: 507-663-1070

Attention: Sales Applications Engineers

Your Name: _____

Email: _____

Phone: _____

Company: _____

Address: _____

ALL FLEX DESIGN CONSIDERATIONS

Please send a pdf or sketch if available. **Note - All of this information is not required to submit a RFQ.** It is simply a guideline. We can provide a formal or budgetary quote as quickly as possible based on the information provided.

Part Number: _____

* **Approximate Part Dimensions:** _____ Inches _____ MM

Number of conductive layers: _____

Smallest Diameter hole: _____

Approximate Overall Thickness: _____

* **Quantity to Quote:** _____

Surface Finish: ☐ HASL ☐ Tin ☐ ENIG ☐ Elec. Gold ☐ OSP
☐ Immersion Nickel ☐ Immersion Silver ☐ Unsure

Does the part require assembly?

- ☐ Yes, but All Flex will not handle the assembly
- ☐ Yes, include assembly pricing (please provide All Flex BOM)
- ☐ No
- ☐ Undetermined

* Indicates required field.

REQUEST FOR QUOTE (RFQ) GUIDELINE

HEATERS

Email To: information@allflexinc.com
or Fax To: 507-663-1070

Attention: Sales Applications Engineers

Your Name: _____

Email: _____

Phone: _____

Company: _____

Address: _____

ALL FLEX DESIGN CONSIDERATIONS

Please provide All Flex with **Heater** CAD data, pdf or sketch if available.

Heater Part Number: _____

* **Approximate Part Dimensions:** _____ Inches OR _____ MM

* **Quantity to Quote:** _____

* **Material construction:** ☐ Polyimide OR ☐ Silicone Rubber

* **Resistance /Input Power** _____
(voltage/amperage/resistance)
important to provide, if known

Temperature range required: _____

Approximate overall thickness: _____

Wires/if any: (length/gauge/insulation): _____

Does the heater require assembly?

☐ Yes, but All Flex will not handle

☐ Yes, include assembly pricing (please provide All Flex BOM)

☐ No

☐ Undetermined

* Indicates required field.

Flexibility to meet customers needs



ISO 9001: 2008 Certified

AS9100 Certified


MIL-P-50884E Qualified

RoHS Compliant

ITAR Registered

UL Recognized

IPC Member



all flex
FLEXIBLE CIRCUITS

1705 Cannon Lane
Northfield, MN 55057

1.877.663.7162
FAX 507.663.1070

E-mail information@allflexinc.com
www.allflexinc.com